

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (previously presented) An X-ray tube, comprising:
an anode assembly, comprising:
a target for emitting X-rays upon irradiation with an electron beam,
a rotor shaft coupled to a motor rotor system and the target, the rotor shaft configured to rotate the target, and
a bearing system supporting the rotor shaft; and
a cathode assembly, comprising:
a cathode configured to emit the electron beam, and
an insulator isolating the cathode from ground potential, wherein the insulator and the motor rotor system are located on the same side of the target and wherein the insulator is generally parallel and radially offset to the rotor shaft.

Claim 2 (original) The X-ray tube of claim 1, wherein the insulator comprises a conical insulator.

Claim 3. (canceled).

Claim 4. (original) The X-ray tube of claim 1, wherein the insulator is offset in a radial direction to the motor rotor system.

Claim 5. (previously presented) The X-ray tube of claim 1, wherein the bearing system distributes load substantially evenly.

Claim 6. (previously presented) The X-ray tube of claim 1, wherein the bearing system straddles the target.

Claim 7. (currently amended) An X-ray tube, comprising:
an anode assembly, comprising:

a target for emitting X-rays upon irradiation with an electron beam,
a rotor shaft coupled to a motor rotor system and the target, the rotor shaft
configured to rotate the target, and
a bearing system supporting the rotor shaft; and
a cathode assembly, comprising:
a cathode configured to emit the electron beam, and
an insulator isolating the cathode from ground potential, wherein the insulator
and the motor rotor system are located on the same side of the target; wherein the X-ray
tube provides axial coverage of up to 80 mm from the focal spot.

Claim 8. (previously presented) The X-ray tube of claim 7, wherein the insulator
comprises a conical insulator.

Claim 9. (canceled).

Claim 10. (previously presented) The X-ray tube of claim 7, wherein the insulator is
offset in a radial direction to the motor rotor system.

Claim 11. (previously presented) The X-ray tube of claim 7, further comprising a
collimator to direct the beam to the subject.

Claim 12. (previously presented) The X-ray tube of claim 7, wherein the bearing
system distributes load substantially evenly.

Claim 13. (previously presented) The X-ray tube of claim 7, wherein the bearing
system straddles the target.

Claim 14-18 (canceled).

Claim 19. (previously presented - withdrawn) A method for CT imaging, the method
comprising:

rotating a gantry about a subject;
emitting X-rays from an X-ray tube mounted on the gantry, wherein the X-ray tube
withstands up to 65 g of stress in operation; and

generating one or more images of the subject based upon the attenuation of the emitted X-rays by the subject.

Claim 20. (previously presented - withdrawn) The method of claim 19, wherein rotating the gantry comprises rotating the gantry at greater than three rotations per second.

Claim 21. (canceled)

Claim 22. (currently amended) An X-ray tube, comprising:
an anode assembly, comprising:

a target for emitting X-rays upon irradiation with an electron beam,

a rotor shaft coupled to a motor rotor system and the target, the rotor shaft configured to rotate the target, and

a bearing system supporting the rotor shaft; and

a cathode assembly, comprising:

a cathode configured to emit the electron beam, and

an insulator isolating the cathode from ground potential; wherein the insulator and the motor rotor system are located on the same side of the target; wherein the X-ray tube provides high-voltage stability of up to 200 kV in operation.

Claim 23. (previously presented) The X-ray tube of claim 22, wherein the insulator comprises a conical insulator.

Claim 24. (previously presented) The X-ray tube of claim 22, wherein the insulator is offset in a radial direction to the motor rotor system.

Claim 25. (previously presented) The X-ray tube of claim 22, wherein the bearing system distributes load substantially evenly.

Claim 26. (previously presented) The X-ray tube of claim 1, wherein the bearing system straddles the target.